

NX-1000 series

NX-1200/1300

VHF/UHF TRANSCEIVERS

NX-1200DE2/1300DE2 DMR
 NX-1200DE3/1300DE3 DMR
 NX-1200NE2/1300NE2 NXDN
 NX-1200NE3/1300NE3 NXDN



5 'i b]j YfgU`fUX]c: DMR + FM Analogue or BL8 B`Ž: A `5 bUc[i Y

If you are thinking of harnessing the latest digital protocols – DMR or NXDN – to enhance business efficiency, the NX-1200/1300 has you covered. Our entry level solution offers the widest selection of two-way radios for everyday use. The models also include basic and keypad variations, with or without a high-contrast backlit LCD. Other features include a 7-colour LED indicator and the popular KENWOOD 2-pin audio accessory connector. Mixed-mode operation ensures seamless integration with legacy radios while smoothing the onward migration path to digital. But whatever your specific needs, audio quality is what determines clear voice communications – which is why KENWOOD radios are used under the most grueling cZconditions, like the cockpit of a racing car. Thanks to our extensive experience with professional systems, reliability is second to none. So whatever your radio requirements, KENWOOD's NX-1200/1300 offers a single platform that's right for you.

● GENERAL FEATURES

- **Wide variations, "One" platform:** To meet various demands — DMR or NXDN digital CAIAD[{ [] } CAIAD[{ [] } models are available
- **Choose from direct & intuitive LCD with standard keypad or basic versions**
- **Easy visible Display: 8-digit LCD** models featuring high-contrast, white backlit LCD
- **Large 7-Colour LED indicator on the top panel**
 - Selective Power-on LED
 - Selective Call Alert LED
 - Battery Level Indication
 - Multi-status function indication
- **RF output power 5W both on VHF/UHF**
- **Wide band UHF 70MHz coverage**
- **Renowned KENWOOD Audio Quality:** TX/RX audio profile with optimisable digital processor
 - Audio Equaliser: Flat, High, Low
 - Auto Gain Control: On, High, Low, Off
 - Noise Suppressor
 - Microphone type settings
- **Multiple Scan Functions;** Dual Priority, Single Priority, Single Zone, Multi, Normal Scan
- **VOX & PTT –triggered Semi- VOX, Voice-operated TX**
- **Emergency Function:** Customisable Emergency Profile
- **Lone Worker**
- **Max / Min Volume setting & Volume control**
- **Voice Announcement**
- **Remote Stun / Kill / Check**
- **Front Panel Programming Mode** (for Keypad model)
- **Electronic Serial Number (ESN)**
- **MIL-STD-810 C/D/E/F/G**
- **IP54 and IP55**
- **Intrinsically safe option (Available later)**

● DIGITAL – NXDN

- FDMA – Very narrow 6.25 kHz & narrow 12.5 kHz bandwidths
- NXDN Conventional Operation
- Site Roaming
- Digital / Analogue Mixed mode
- Group / Individual Call
- Status / Short data, Paging Call
- Remote Stun / Kill, Monitor, Check & Control
- Digital Bit Scrambler
- Late Entry
- Over-the-Air Alias (OAA)

● DIGITAL – DMR

- TDMA 2-slot 12.5 kHz bandwidth equivalent to 6.25 kHz very narrow bandwidth
- DMR Tier II Conventional Operation
- Site Roaming
- DMR Auto Slot Select
- Dual Slot Direct Mode
- Digital / Analogue Mixed mode
- Call Interruption
- Group / Individual Call
- Status / Short data, Paging Call
- Remote Stun / Kill, Monitor, Check & Control
- Enhanced Encryption (ARC4)
- Digital Bit Scrambler
- Late Entry
- Over-the-Air Alias (OAA)

● ANALOGUE - FM

- FM Conventional Operation
- FleetSync: PTT ID, Stun/Revive, Talk back, Selcall
- MDC1200: PTT ID, Radio Inhibit/Uninhibit, Radio check, Emergency
- QT / DQT, DTMF, 2-tone, 5-tone
- Built-in Programmable Voice Inversion Scrambler (per channel)
- Built-in Compander (per channel)



Standard Keypad model

Basic model

NX-1200DE2/1300DE2
 NX-1200NE2/1300NE2

NX-1200DE3/1300DE3
 NX-1200NE3/1300NE3

OPTIONAL ACCESSORIES

- **KNB-45L/69L**
Li-ion BATTERY PACK (7.4 V/2000 mAh, 7.4 V/2450 mAh)
- **KNB-53N**
Ni-MH BATTERY PACK (7.2 V/1400 mAh)
- **KNB-82LC**
Li-ion BATTERY PACK (7.4 V/1900 mAh, Intrinsically Safe)*
*Available later
- **KSC-35S**
RAPID CHARGER (for Li-ion KNB-45L/69L/82LC)
- **KSC-43**
RAPID CHARGER (for Li-ion KNB-45L/69L/82LC & Ni-MH KNB-53N)
- **KSC-356A**
MULTIPLE CHARGER
(6-pocket for Li-ion KNB-45L/69L/82LC)
- **KSC-35SCR**
CHARGER POCKET (6-pocket for KMB-35A)



- **KMB-35A**
MULTI CHARGER ADAPTER (for KSC-35SCR)
- **KVC-22**
DC VEHICULAR CHARGER ADAPTER (for KSC-35S)
- **EMC-11/12**
CLIP MICROPHONE WITH EARPHONE (STD, EAR-HANGING)
- **KHS-35F**
HEADSET (EAR-HOOK)
- **KMC-45D**
SPEAKER MICROPHONE



- **KRA-22/23**
VHF/UHF HELICAL ANTENNA (Low Profile)
- **KRA-26**
VHF HELICAL ANTENNA (Standard Length)
- **KRA-27**
UHF WHIP ANTENNA (Standard Length)
- **KRA-41/42**
VHF/UHF STUBBY ANTENNA
- **KBH-10**
BELT CLIP



All accessories and options may not be available in all markets. Contact an authorised KENWOOD dealer for details and complete list of all accessories and options.

SPECIFICATIONS

| GENERAL | | NX-1200 | NX-1300 |
|--|-------------------|----------------------------|-------------|
| Frequency Range | | 136-174 MHz | 400-470 MHz |
| Max. Channels per Radio | | 260 (64 for no LCD models) | |
| Number of Zones | | 128 (4 for no LCD models) | |
| Max. Channels per Zone | | 250 (16 for no LCD models) | |
| Channel Spacing | Analogue | 25 / 20 / 12.5 kHz | |
| | Digital | 12.5 / 6.25 kHz | |
| Power Supply | | 7.5 VDC ±20 % | |
| Battery Life (5-5-90) | | TDMA | FDMA |
| | KNB-45L | 14.5 H | 11 H |
| | KNB-53N | 10 H | 7 H |
| | KNB-69L | 19 H | 14 H |
| Operating Temperature | | -30°C to +60°C | |
| Frequency Stability (-30 to +60°C; +25°C Ref.) | | ±0.5 ppm | |
| Dimensions (W x H x D) / Weight (net) | Radio only | 54 x 123 x 33.5 mm / 175 g | |
| | With KNB-45L/82LC | 54 x 123 x 33.5 mm / 295 g | |
| | With KNB-53N | 54 x 123 x 33.5 mm / 365 g | |
| Projections not included; for Std keypad model | With KNB-69L | 54 x 123 x 37.5 mm / 310 g | |

Specifications are measured according to applicable standards. Specifications shown are typical and subject to change without notice, due to advancements in technology. Details and timing of firmware and software updates are subject to change without notice.

| RECEIVER | | NX-1200 | NX-1300 |
|---|--|--|---------|
| Sensitivity | NXDN@12.5/6.25 kHz 1 % BER | -4.4 dBµV _{emf} (0.30 µV) / -6.4 dBµV _{emf} (0.24 µV) | |
| | NXDN@12.5/6.25 kHz 3 % BER | -6.4 dBµV _{emf} (0.24 µV) / -8.4 dBµV _{emf} (0.19 µV) | |
| | DMR@12.5 kHz 1 % BER | -5.0 dBµV _{emf} (0.28 µV) | |
| | DMR@12.5 kHz 5 % BER | -8.0 dBµV _{emf} (0.20 µV) | |
| | Analogue (12 dB SINAD) (25/20/12.5 kHz) | -5.7 dBµV _{emf} (0.26 µV) / -5.4 dBµV _{emf} (0.27 µV) / -7.1 dBµV _{emf} (0.22 µV) | |
| Analogue (20 dB SINAD) (25/20/12.5 kHz) | -3.9 dBµV _{emf} (0.32 µV) / -3.6 dBµV _{emf} (0.33 µV) / -3.6 dBµV _{emf} (0.33 µV) | | |
| Selectivity | Analogue@ 25/20/12.5 kHz | 74 / 72 / 67 dB | |
| Intermodulation | | 65 dB | |
| Spurious Rejection | | 70 dB | |
| Audio Distortion | | 7 % | |
| Audio Output (Internal) | | 1 W | |
| TRANSMITTER | | NX-1200 | NX-1300 |
| RF Power Output | | 5 / 4 / 2.5 / 1 W | |
| Spurious Emission | | <1GHz ≤ -36dBm, 1GHz - 4GHz ≤ -30dBm | |
| FM Hum & Noise | Analogue@25/20/12.5 kHz | 45 / 45 / 40 dB | |
| Audio Distortion | | 2 % | |
| DMR Digital Protocol | | ETSI TS 102 361-1, -2, -3 | |
| Emission Designator | | 16K0F3E, 14K0F2D, 14K0F3E, 12K0F2D, 11K0F3E, 8K50F3E, 7K50F2D, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D, 7K60FXE, 7K60FXD | |

MIL-STD & IP

| MIL Standards | Methods / Procedures | | | | |
|------------------------------------|----------------------|----------------|----------------|---------------|---------------|
| | 810C | 810D | 810E | 810F | 810G |
| Low Pressure | 500.1/ I | 500.2/ I, II | 500.3/ I, II | 500.4/ I, II | 500.5/ I, II |
| High Temperature | 501.1/ I, II | 501.2/ I, II | 501.3/ I, II | 501.4/ I, II | 501.5/ I, II |
| Low Temperature | 502.1/ I | 502.2/ I, II | 502.3/ I, II | 502.4/ I, II | 502.5/ I, II |
| Temp. Shock | 503.1/ I | 503.2/ I | 503.3/ I | 503.4/ I, II | 503.5/ I |
| Solar Radiation | 505.1/ I | 505.2/ I | 505.3/ I | 505.4/ I | 505.5/ I |
| Rain ² | 506.1/ I, II | 506.2/ I, II | 506.3/ I, II | 506.4/ I, III | 506.5/ I, III |
| Humidity | 507.1/ I, II | 507.2/ II, III | 507.3/ II, III | 507.4 | 507.5/ II |
| Salt Fog | 509.1/ I | 509.2/ I | 509.3/ I | 509.4 | 509.5 |
| Dust | 510.1/ I | 510.2/ I | 510.3/ I | 510.4/ I, III | 510.5/ I |
| Vibration | 514.2/ VIII, X | 514.3/ I | 514.4/ I | 514.5/ I | 514.6/ I |
| Shock | 516.2/ I, II, V | 516.3/ I, IV | 516.4/ I, IV | 516.5/ I, IV | 516.6/ I, IV |
| International Protection Standards | IP54, 55 | | | | |
| Dust & Water ² | IP54, 55 | | | | |

²To meet MIL-810 and IP grade, audio accessory connector must be covered.

- NXDN™ is a trademark of JVCKENWOOD Corporation and Icom Inc. • FleetSync® is a registered trademark of JVCKENWOOD Corporation.
- All other trademarks are the property of their respective holders.

JVCKENWOOD U.K. Limited

<https://kenwoodcommunications.co.uk/>



ISO9001 Registered

Communications Systems Division

JVCKENWOOD Corporation

CL877E-E-2